

**SDA
(HASTE ROSCA FEMEA)**



**SDA - B
(HASTE ROSCA MACHO)**



ESPECIFICAÇÕES										
∅ (mm)	12	16	20	25	32	40	50	63	80	100
ALIMENTAÇÃO	M5X0,8				1/8"		1/4"		3/8"	
ACIONAMENTO	DUPLA AÇÃO									
PRESSÃO TRAB.	1 a 9 bar									
PRESSÃO MAX.	10,5 bar									
TEMP. TRABALHO	- 10 a 80 °C									

∅ mm	CURSO PADRÃO (mm)																
	5	10	15	20	25	30	40	50	80	100	125	160	200	250	320	400	500
12	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X	X	X
16	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X	X	X
20	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X	X	X
25	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X	X	X
32	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X
40	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X
50	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	X	X
63	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
80	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
100	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•